

AMBIR™

DB100/BR100 User Guide

Register your product



V2.1.20.1126



Software version number.

www.ambir.com

©2022 Ambir Technology Inc. All rights reserved. The Ambir logo is a trademark of Ambir Technology Inc. Features, specifications and bundled software application(s) and/or version numbers of software applications are subject to change without notice. Windows is a registered trademark of Microsoft Corporation in the United States and other countries. All trademarks and registered trademarks are the property of their respective owners.

1. Reset to default



Factory default

PLEASE NOTE: By scanning the "Factory default" settings code, all settings of the barcode scanner will be restored to factory default settings. Codes marked "*" below are the default settings.

2. Interface setting



USB Keyboard

3. Output setting



* Add "Enter"



Remove "Enter"



Add newline



*Remove newline

4. Case switching



* Default case setting



All lowercase



All uppercase

5. Beeper setting



*On



Off

6. Language output setting for USB HID

The default is English, but other languages can be set.



*Default



For Microsoft Excel & Notepad

The keyboard mode supports output of other languages by scanning the corresponding configuration code. (The default is English, but other languages can be input)



For Microsoft Word

7. Language



*USA



Spain



Italy



Singapore



Salvador



Japan



Thailand



Belgium



Sierra Leone



Turkey

7. Language (Continued)



Russia
"windows1251"



Russian
"Shift-jis"



Hungary



Germany



Algeria & Arabic



Spanish Latin



British



France



FULL ASCII

8. Barcode setting

2D handheld barcode scanner default enable.



Enable url QR code



Disable url QR code

2D desktop barcode scanner default disable.

9. Notice

1. Scanner cannot be activated.

Check whether the cable is firmly connected (there will be a crisp sound after the USB cable is connected to the device) and then check whether the USB is properly connected to the device. If it is not powered on, then try to connect the USB port behind the host.

2. Data is not uploaded.

Check whether the USB cable is successfully connected to the computer. If it is connected correctly, there will be a prompt sound. The driver installation will appear when connecting to the computer for the first time. After the driver is automatically installed, scan the code to test whether there is a decoding prompt sound.

If the decoding is normal, please scan the USB Keyboard in this Setup manual.

If there is no response after scanning the code, please scan "Recall default" and then plug it in again.

If there is no response after re-powering, or no response after scanning the setting code, please contact the dealer's for technical support.

10. Use equipment correctly

Please use the scanner after the device has finished booting to prevent the device from being unable to recognize the scanner or causing the device to start abnormally. (You can try re-plug the device to solve this problem)

The following is the test barcode, which is used for transmission test.



2D barcode test

12345678



1D barcode test

3 123456789019