nSign™ SP110

AMBIR®

4.7"
(119.38mm)

0.4"
(10.16mm)

6.3" (160.02mm)

The AMBIR nSign SP110 eSignature Solution is sculpted to carefully fit the hand of the signer, and its compact size allows it to fit on virtually any desk or in any travel bag.

Natural Capture Technology.
Each signature has its own personality. The AMBIR nSign SP110 captures every nuance with pressure-sensitive "Natural Capture" technology.

Customizable Options.
With the included Slideshow Manager application, anyone can upload their logo or promotional material for more impressions at high-traffic areas.

Secure Your Signatures.
You can trust built-in AES encryption, RSA signaling and signature biometrics to keep every signature locked up tight.

Flexible Save Options.
Save signatures in TIFF, PNG, BMP, JPEG or GIF format

TWAIN / WIA Drivers.
The AMBIR nSign SP110 can function via TWAIN or WIA driver, much like a scanner. With TWAIN and WIA, it's simple to change resolution, rotate and crop signatures.

nSign™ SP110

Backlit 4 x 2″ eSignature Pad

Sku # SP110-S2
MSRP: $399.95

2 YEARS WARRANTY

INCLUDES LIMITED PART & LABOR COVERAGE WITH COMPREHENSIVE U.S.–BASED PHONE & CHAT SUPPORT

2025_V_1

signoSign 2 Software.
Designate exactly where you'd like PDFs to be electronically signed. It makes no difference whether the signature fields change or move from page to page: signature areas are defined by word association, not spatial coordinates.

signoSign 2 also integrates your newly-signed documents directly into your workflow processes by automatically emailing PDFs to specified recipients. The addresses can even be extracted directly from the document itself.

Creating index data for automated processing is also simple with signoSign 2. Whether it's an order number, a service request or a customer's account information, it can be defined for automatic indexing.

signoIntegrator 2.
Accessible immediately through the Windows System Tray, signoIntegrator 2 lets you import signatures into any Windows application with one click.

signoImager 2.
A dead-simple way to capture a quick signature, save it in TIFF, PNG, BMP, JPEG or GIF format and adjust settings like line thickness and resolution.

Specifications

Active Signing Area
4 x 2"

Dimensions
4.7" x 6.3" x 0.4" (119.38mm x 160.02mm x 10.16mm)

Weight
8.11 oz (230g)

Display Graphics
up to 320 x 160 pixels

Resolution
4.096 x 4.096 Pixel absolute 2.214 x 1.130 ppi

Security
AES encryption, RSA signing, signature biometrics, RSA encryption inside the pad

Supported OS
Windows 10/11

Sensor Type
RTP (Resistive-Touch-Panel)

Pen
Pen with special, resilient pen tip (changeable)

Surface
Special foil surface for RTP sensors

Life expectancy
Approximately 1 Million Signatures

Pressure Stages
1.024

Sample Rate
500 Hz, 4D Samples (x, y, z, t)

Stylus is Included, Not Proprietary

Citrix Ready

USB Connection, No Driver Installation Required

Stylus is Included, Not Proprietary

Scratch-Resistant Surface

Ergonomic Design

TAA Compliant

2-Year Warranty